

# ClearPath Forward® Libra 4690

## Product Information Sheet

### Mid-range ClearPath® MCP processing

Unisys is committed to delivering ClearPath® MCP systems that are designed to meet the needs of our clients with large, essential business workloads. The ClearPath Forward® Libra 4690 system delivers:

- Unmatched security delivered through integrated hardware and software design
- Advanced system availability with multiple levels of component redundancy
- Fully compatible with existing MCP applications and data formats
- Flexible pay-for-use licensing

The Libra 4690 system is designed and built with the highest levels of system resiliency and availability in mind. Each primary system component maintains internal resiliency characteristics for power, cooling, local disks and memory.

The Libra 4690 systems provide a complete unified solution where Unisys integrates, tests and supports all components.

The Libra 4690 system's resiliency is further enhanced by including redundant processors, I/O subsystems and supporting infrastructure components.

### ClearPath MCP mid-range performance

The mid-range performing ClearPath Forward Libra 4690 systems are one of the latest generations of enterprise-class systems to support the MCP operating system on Unisys Intel® platforms. The main processing memory module, or PMM, provides a single thread performance of 550 MIPS and a single MCP image of up to 2,200 MIPS.

Separate Intel-based I/O storage modules, or ISMs, can be combined to deliver over 90,000 I/Os per second.


The Libra 4690 system is licensed following the Unisys pay-for-use business model and utilizes our advanced metering technology.

Metering technology enables you to instantly take advantage of the Libra 4690 full processing capacity while only being charged for the resources used. Pay-for-use licensing allows a reduced capital investment, with a better match of revenues to expenses.

### Flexible and secure architecture

The ClearPath Forward Libra 4690 system architecture uses multiple Unisys Intel-based components integrated through a high-speed, private LAN interconnect. This modular design provides inherent redundancy of all components and allows scalable configurations of the I/O subsystem.

The PMM executes the ClearPath MCP instruction set and includes a full 6GW of memory.



Multiple high-speed Ethernet connections are maintained within the PMM to provide MCP network connectivity.

Two PMMs are included in every Libra 4690. As one PMM is actively processing the MCP workload, the second PMM acts as a warm standby. This two PMM design allows a quick failover of the MCP processing environment and improves system availability during scheduled maintenance.

The Libra 4690 systems also include two I/O Service Modules, or ISMs. Each ISM supports multiple high-speed I/O interfaces to a variety of storage types and for network connections. The latest storage card options supported in the ISM include quad-port 32Gb Fibre connections.

Support for 10/25Gb Ethernet network interface cards allows the Libra 4690 to be part of a high-speed client network, and a full range of copper or optical 1Gb and 10Gb NICs are available.

Each of the two ISMs may be configured with a connection to a shared storage device. This redundancy ensures a balanced I/O flow and ensures that MCP workloads will continue even if one ISM is unavailable.

Unique Libra firmware has been developed for the Libra 4690 PMM and ISM modules to provide compatibility with previous Libra architectures. Existing MCP application code will run without re-compiling or relinking. Supported storage devices can be connected to the Libra 4690 I/O subsystem, and data formats will be maintained.

The Libra 4690 system demonstrates the Unisys ClearPath commitment to unparalleled security. Multi-layered security is inherent to the architecture; providing protection that helps you maintain data integrity, reduce operational costs, and minimize the risk of lost revenue, regulatory sanctions or a diminished reputation.

## ClearPath MCP integrated stack

The ClearPath Forward Libra 4690 system delivers an integrated stack consisting of hardware, software, middleware and applications optimized for reliability, security, scalability and performance.

A set of powerful enterprise integration capabilities allows existing ClearPath MCP applications and data to expose new services and enable the Libra 4690 system to participate in digital transformation initiatives. In addition, a rich set of industry-standard middleware technologies are available for integrating ClearPath MCP data and transactions.

The ClearPath MCP release 20.0 is the minimum release level required to support the ClearPath Forward Libra 4690 system. Each MCP release is comprised of more than 100 integrated system software products, delivering the operating system, databases, transaction management, development, and many other software elements to support enterprise-class solutions.

## Software interdependencies

The ClearPath Forward Libra 4690 system requires ClearPath MCP Release 20.0 or later.

## Maximizing your ClearPath Forward Libra investment

Unisys recognizes that you are looking for a complete end-to-end solution to satisfy critical IT needs. For ClearPath Forward Libra systems, Unisys offers a single source for integration, support, education, and services.

Additional ClearPath Forward Services maximize your investment in ClearPath Forward systems, applications, tools, and skills. These services help you to implement our solutions, increase the value of your core business applications, and simplify the operation and administration of your ClearPath Forward installation.

## Technical specifications

Key Hardware Solution Features	ClearPath Forward Libra 4690 System	
<b>Form Factor</b>	<i>Cabinet</i>	42U rack
<b>MIPS Performance Level (See Note 1 below)</b>	<i>Single Thread Processor MIPS</i>	550
	<i>Pay-for-Use Business Model</i>	Libra 4690 (50 – 1,540 MIPS/month with 2,200 MIPS Ceiling)
<b>Processor Memory Module (PMM), I/O Storage Module (ISM)</b>		<b>Unisys x600 R760 - Quantity (2) Processor Memory Module (PMM) (Active/Standby)</b>
	<i>Sockets / Processors / Chipset</i>	(2) / (2) Intel® Xeon Platinum 8462Y+, 32C, 2.8 GHz, 60.0 MB Cache, DDR5 Up To 4800 MT/s, 300W Td
	<i>Memory</i>	512GB Memory; (32) 16GB, Low Volt, Dual Rank x4, 4800MT/s RDIMMs
	<i>Internal Storage</i>	(2) 1.6TB NVMe Hot-plug Storage (note: no user internal storage) RAID 1 for H965i Controller
		<b>Unisys x600 R760 - - Quantity (2) I/O Service Module (ISM)</b>
	<i>Sockets / Processors / Chipset</i>	(2) / (2) Intel® Xeon Platinum 8462Y+, 32C, 2.8 GHz, 60.0 MB Cache, DDR5 Up To 4800 MT/s, 300W Td
	<i>Memory</i>	256GB Memory; (16) 16GB, Low Volt, Dual Rank x4, 4800MT/s RDIMMs
	<i>Internal Storage</i>	(2) 1.6TB NVMe Hot-plug Storage (note: no user internal storage) RAID 1 for H965i Controller
		<b>Common Attributes – PMM and ISM</b>
	<i>Form Factor</i>	2U
	<i>Internal Interconnect</i>	3 x Intel Ultra Path Interconnect (UPI) links; 16 GT/s
	<i>RAID Controller</i>	PERC H965i Integrated RAID Controller, 8GB NV Cache, Front card
	<i>Power</i>	Dual, Hot-plug, Redundant Power Supply (1+1), 1400W
<i>Availability and Maintainability Features</i>	Hot-plug drive bays; Hot-plug redundant fan; Interactive LCD screen; Extended thermal support; Extended power range	
<b>Operations Server</b>		<b>Unisys x600 R350 - Quantity (2) Operations Servers (OPS)</b>
	<i>Form Factor</i>	1U
	<i>Sockets / Processors</i>	(1) Intel® Xeon® processor E-2336, 2.9GHz, 6C (65W)
	<i>Memory</i>	16GB; (2) 8GB, DDR4 3200 MT/s UDIMMs
	<i>Internal Storage</i>	(2) 1.9TB, 2.5" SSD 6Gbps Hot-plug (Note: no user internal storage)
	<i>RAID Controller</i>	PERC H355 RAID Controller
<i>Power</i>	Dual Hot-plug Redundant Power Supply (1+1), 600W	

Note 1: Performance information based on Unisys benchmarks under standard conditions.

Common Solution		Attributes
Environmental Specifications (temperature, humidity, altitude de-rating)	<b>Continuous Operation (PMM, ISM, OPS)</b>	5°C to 40°C at 5% to 85% RH with 29°C dew point. De-rate maximum allowable temperature by 1°C per 175 m above 950 m (1°F per 319 ft).
	<b>Storage (PMM, ISM, OPS)</b>	-40°C to 65°C (-40°F to 149°F) with a maximum temperature gradation of 20°C per hour at 10% to 95% relative humidity at a maximum wet bulb temperature of 33°C (91°F); atmosphere must be condensing at all times.
	<b>Expanded Operation</b>	When operating in the expanded temperature range, system performance may be impacted, and ambient temperature warnings may be reported on the LCD and in the System Event Log.  <b>Expanded operation restrictions:</b>  No cold startup below 5°C Maximum altitude for the operating temperature must be 3050m (10,000 ft)
<b>Maximum Heat Dissipation</b>		Single Partition, 2 PMM, 2 ISM, 2 OPS: 14,908 BTU/hr. (max)
Cabinet	<b>External Metrics Per Cabinet</b>	US: H(78.39 in), W(23.62 in), D(47.25 in) Metric: H(199.1 cm), W(60.0 cm), D(120.0 cm)
	<b>Chassis Weight (max)</b>	Single Partition, 2 PMM, 2 ISM, 2 OPS: 950 lbs. (430.9 kg) shipping weight
Power	<b>Supply Voltage</b>	100 - 240VAC
	<b>Current Consumption</b>	System: 25.85A @200VAC
	<b>Frequency</b>	50-60Hz
<b>Cooling</b>		Capability to operate at excursion-based temperatures beyond the industry standard of 35°C (95°F). N+1 fan redundancy allows continuous operation with one fan failure in the unit.
Altitude	<b>Operating / Storage (PMM, ISM, OPS)</b>	--16m to 3,048m (-50 ft to 10,000 ft) / -16m to 12,000m (-50 ft to 39,370 ft)
<b>Airborne Contaminant Level</b>		Class G1 or lower as defined by ANSI/ISA71.04-2013
<b>Thermal and Acoustics</b>		Thermal management delivers high performance for the right amount of cooling to components at the lowest fan speeds across a wide range of ambient temperatures from 10°C to 30°C (50°F to 86°F) and to extended ambient temperature ranges.
<b>Remote Management</b>		Embedded Remote Management interface provides server-level management that monitors, reports, and controls power consumption at the processor, memory, and system level.
<b>System Management</b>		IPMI 2.0 compliant
<b>Industry Compliance</b>		Compliant with all relevant industry certifications and guidelines, including 80 PLUS, Climate Savers and ENERGY STAR.

**Note:** These specifications do not provide a viable substitute for a detailed configuration, environmental, and infrastructure planning study.

For more information, visit [www.unisys.com/clearpath](http://www.unisys.com/clearpath)



[unisys.com](http://unisys.com)

© 2024 Unisys Corporation. All rights reserved.

Unisys and other Unisys product and service names mentioned herein, as well as their respective logos, are trademarks or registered trademarks of Unisys Corporation. All other trademarks referenced herein are the property of their respective owners.